

3-29-00

A



ATTORNEY DOCKET NO.  
111111.1111

PATENT APPLICATION

APPLICATION FOR U.S. PATENT UNDER 37 C.F.R. § 1.53(b)  
TRANSMITTAL FORM



Box Patent Application  
ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application  
of:

Inventors or Application Identifier: Russell W. White, et al.

Entitled: **SYSTEM AND METHOD FOR COMMUNICATING  
SELECTED INFORMATION TO AN ELECTRONIC DEVICE**

Enclosed are:   X   Specification (50 pages)  
  X   Drawing(s) (9 Sheets Informal)

  X   Signed Declaration.

       Information Disclosure Statement (IDS) PTO-1449 with copies  
of references cited.

  X   Certificate of Mailing

  X   Return Receipt Postcard

       An Assignment of the invention to                     . is attached.  
A cover sheet in compliance with 37 C.F.R. §§ 3.28 and 3.31 is  
included with the Assignment recordation fee of \$40.00 pursuant  
to 37 C.F.R. § 1.21(h).

Verified Statement Claiming Small Entity Status - Independent  
Inventors is enclosed.


Attorney's Docket:  
111111.1111  
Page 2

PATENT APPLICATION

FEE CALCULATION					FEE
	Number		Number Extra	Rate	Basic Fee
					\$ 345.00
Total Claims:	25	- 20 =	5	X \$9 =	\$ 45.00
Independent Claims	4	- 3 =	1	X \$39 =	\$ 39.00
TOTAL FILING FEE =					\$ 429.00

Enclosed is a check in the amount of \$429.00 to satisfy  
filing fee requirements under 37 C.F.R. § 1.16.

Respectfully submitted,

  
Kevin R. Imes  
Reg. No. 44,795

Date: March 28, 2000

Correspondence Address:  
Russell W. White  
10704 Redmond  
Austin, Texas 78739  
(512) 301-5518

Applicant or Patentee: Russell W. White, et. al.

Serial or Patent No:

Attorney's  
Docket No. 111111.1111

Filed or Issued:

March 28, 2000

Title:

**System and Method for Communicating Selected Information to an Electronic Device**

VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY STATUS  
(37 CFR 1.9(f) and 1.27(b)) -- INDEPENDENT INVENTOR

As below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office regarding the invention entitled .

☒ the specification filed herewith.  
☐ application serial number \_\_\_\_\_, filed \_\_\_\_\_.  
☐ patent number \_\_\_\_\_, issued \_\_\_\_\_.

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below.\*

☐ No such person, concern, or organization  
☐ Persons, concerns or organizations listed below\*

\*NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)

NAME: Russell W. White  
ADDRESS: 10704 Redmond  
Austin, Texas 78739

☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

NAME: Kevin R. Imes  
ADDRESS: P.O. Box 208  
Pflugerville, Texas 78691-0208

☒ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

NAME:  
ADDRESS:

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION


NAME:  
ADDRESS:

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).


I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Russell W. White  
NAME OF INVENTOR

  
Signature of Inventor

3/28/00  
Date

Kevin R. Imes  
NAME OF INVENTOR

  
Signature of Inventor

March 28, 2000  
Date

ATTORNEY DOCKET NO.  
111111.1111

PATENT APPLICATION

1

SYSTEM AND METHOD FOR COMMUNICATING  
SELECTED INFORMATION TO AN ELECTRONIC DEVICE

TECHNICAL FIELD OF THE INVENTION

The present disclosure relates in general to the field of wireless communication, and more particularly to a system and method for communicating selected information to an electronic device.

5

BACKGROUND OF THE INVENTION

The first commercial radio stations in the United States began operation around 1920. Today, there may be as many as 12,000 radio stations in the United States programming in several distinct formats. When broadcasting their respective signals, these radio stations often use an analog signal, which may be modulated based on frequency or amplitude. Frequency modulated (FM) radio appears to be the dominant entertainment medium while amplitude modulated (AM) radio seems to be a popular outlet for news and information.

Unfortunately, analog radio may be unable to provide the sound quality and consistency that radio listeners desire. As such, several broadcasting related companies have begun to consider a movement to digital radio. Unlike analog radio reception, digital radio reception may be able to provide compact disk (CD) quality sound while remaining virtually immune to interference. Being immune to interference may result in reducing static growls or 'multipath' echoes, echoes caused by signal reflections off buildings or topographical features.

Some countries, like Canada and many European countries, may choose to have digital radio operate in a single digital radio band such as the L-band between 1452-1492 megahertz (MHz). This band would allow the reception of both terrestrially and satellite-originated signals. By comparison, FM radio typically operates between 88 and 108 MHz while AM radio typically operates between 0.525 and 1.705 MHz. Neither of these bands allows for easy transmission via satellite.

Canada proposed using the L-Band for digital radio as early as 1992. Several countries throughout the world

have since agreed to use the L-Band for digital radio with one notable exception. It appears the United States has chosen not to operate its digital radio within the L-Band. In the United States, the L-Band may already be committed for military uses. Apparently, the United States plans to adopt a system called in-band on-channel, or IBOC, which fits within the AM and FM frequencies.

IBOC technology may offer some advantages over L-Band transmissions. For example, there may be no need for new spectrum allocations. There may be backward and forward compatibility with existing AM and FM systems on both the transmitter and receiver sides, and there may be a low-investment upgrade to digital systems. Unfortunately, a workable IBOC solution is yet to be seen though technology may someday make IBOC digital radio commercially possible.

Even if an IBOC solution becomes commercially available in the United States, IBOC digital radio may suffer from several shortcomings. For example, there may be global standardization problems. Though the United States favors IBOC, the European and Canadian communities seem to favor L-Band making the establishment of a global standard difficult.

SUMMARY OF THE INVENTION

In accordance with teachings of the present disclosure, a system and method for communicating selected information to an electronic device are disclosed that provide significant advantages over prior developed systems. The disclosed embodiments allow a radio listener to create a personal playlist and to listen to this playlist in a wireless atmosphere while enjoying CD quality sound.

According to one aspect of the present disclosure, a system incorporating teachings of the present invention may include a digital engine operable to maintain data representing the selected information in a digital format. In some embodiments, the digital engine may be communicatively coupled to a graphical user interface that allows a user to identify the selected information. The system may also include a communication engine communicatively coupled to the digital engine, the communication engine may be operable to wirelessly communicate the data representing the selected information to an electronic device.

The wireless communication may involve communicating via a cellular communications network. The cellular communications network may be, for example, the global system for mobile communications network (GSM), which may operate around 1.8 GHz or 1.9 GHz. The cellular communications network may also involve, for example, the code-division multiple access network (CDMS). In some embodiments, the wireless communication may involve communicating via a high-speed, low-power microwave wireless link. For example, the wireless link may

include a Bluetooth link, which may operate around 2.4 GHz.

According to another aspect of the present invention, a system for communicating selected information to an electronic device is disclosed. The system includes a digital engine operable to maintain data associated with selected audio information and a communication engine communicatively coupled to the digital engine, the communication engine operable to initiate wireless communication of the data to the electronic device.

According to another aspect of the present invention, a method for communicating selected audio information to an electronic device is provided. The method includes maintaining data associated with the selected audio information using a digital engine, and initiating wireless communication of the data to the electronic device.

According to another aspect of the present invention, an electronic device for receiving selected audio information via wireless communication is provided. The device includes a communication module operable to receive wireless communication of the selected audio information, a storage medium operably coupled to the communication module, the storage medium operable to store the selected audio information, and a processor module coupled to the communication module, the processor module operable to process the received selected audio information.

According to another aspect of the present invention, a method for communicating selected audio information to an electronic device is provided. The



method includes presenting information associated with  
audio information within an interface associated with a  
communication network, receiving an input from a user  
identifying the selected information, maintaining data  
5 associated with the selected audio information using  
digital engine, and initiating wireless communication of  
the data to the electronic device.

According to a particularized aspect of the present  
invention the interface operates in a browsing  
10 environment and the wireless communication operates  
outside the browsing environment.

Other technical advantages will be apparent to those  
of ordinary skill in the art in view of the following  
specification, claims, and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present  
embodiments and advantages thereof may be acquired by  
referring to the following description taken in  
5 conjunction with the accompanying drawings, in which like  
reference numbers indicate like features, and wherein:

FIGURE 1 depicts a general system for wirelessly  
communicating selective information to an electronic  
device in accordance with one aspect of the present  
10 invention;

FIGURE 2 illustrates a block diagram of a method of  
wirelessly communicating selected information to an  
electronic device;

FIGURE 3 illustrates an electronic device operable  
15 to receive selected audio information in accordance with  
the teachings of the present invention;

FIGURE 4 illustrates a graphical user interface  
(GUI) for displaying selectable audio information  
according to one aspect of the present invention;

20 FIGURE 5A illustrates a portable radio system having  
a mount for an electronic device according to one  
embodiment of the present invention;

FIGURE 5B illustrates automobile console having a  
mount for coupling an electronic device according to one  
25 aspect of the present invention;

FIGURE 6 illustrates a block diagram of a system for  
communicating voice mail messages using email according  
to one embodiment of the present invention;

FIGURE 7 illustrates a flow chart for providing  
30 voice email messages according to one embodiment of the  
present invention;

FIGURE 8 illustrates a flow diagram of a method for providing selected audio information to an electronic device according to one embodiment of the present invention; and

5       FIGURE 9 illustrates an automobile console having a mount for an electronic device according to one embodiment of the present invention.

111111.1111

DETAILED DESCRIPTION OF THE INVENTION

The conceptual groundwork for the present invention includes wirelessly communicating selective information to an electronic device. According to one aspect, a user  
5 may interact with the Internet to select information, such as audio information, and wirelessly communicate the selected information to an electronic device. The electronic device receives the information via a wireless communications network and processes the information  
10 accordingly. In a particularized form, a user may select information from an Internet website operable to allow selectivity of audio information such a songs, on-line radio stations, on-line broadcasts, streaming audio, or other selectable information. Upon selecting the audio  
15 information, information or data associated with the selected audio information is wirelessly communicated to an electronic device. The electronic device may then be used to process the selected audio information. In this manner, a user may receive selective audio information  
20 via a wireless electronic device.

In one form, the electronic device may be operable to communicate with an individual's automobile audio system. A user may select audio information utilizing a personal computer with access to a website operable to  
25 display selectable audio information. The selected audio information may then be wirelessly communicated to the electronic device associated with an automobile's audio system. Therefore, upon receiving the selected audio information, a user may access and play the received  
30 audio information utilizing the electronic device in association with the automobiles audio system.

The present invention is not limited to communicating only audio information. One skilled in the art can appreciate that other types of information, such as video, textual, etc. may be communicated utilizing the systems and methods disclosed herein without departing from the spirit and scope of the present invention. Additionally, it will be understood that information may be formatted in a plurality of ways at different phases of communication without losing the underlying content of the selected information. For example, an audio file may be formatted, segmented, compressed, modified, etc. for the purpose of providing or communicating the audio invention. Therefore, the term 'audio information' or 'information' is used in a general sense to relate to audio information in all phases of communication.

FIGURE 1 depicts a general system for wirelessly communicating selective information to an electronic device in accordance with one aspect of the present invention. The system, illustrated generally at 100, includes a digital engine 101 coupled to a communications engine 102. Communications engine 102 is remotely coupled to an electronic device 103. Digital engine 101 may be directly or indirectly coupled to storage device 105 operable to store information.

Digital engine 101 maintains information or data associated with selected information in a digital format. The information may be stored within storage device 105 or other storage devices operable to maintain data or information associated with the selected information. Communications engine 102 is communicatively coupled to digital engine 101 and operable to wirelessly communicate the selected information to electronic device 103.

During operation, audio information may be selected by a user utilizing a personal computer or other devices operable to communicate with an information network. Digital engine 102 is operable to maintain information associated with the selected audio information. For example, the information could be several songs or titles configured as an audio file and formatted in a digital format such as an MP3 file, wave file, etc. The maintained information may also be a reference to a network location where an audio file may be stored, a network location where a network broadcast of audio information may be located, etc. or other network locations having information associated with the selected audio information. Therefore, digital engine 101 may maintain a plurality of different types of information or data associated with the selected audio information. System 100, utilizing communication engine 102, may wirelessly communicate data or information associated with the selected audio information to electronic device 105 thereby providing wireless communication of selected information to an electronic device operable to receive wireless communications.

In one embodiment, digital engine 101 may be used in association with an Internet website configured to provide access to selectable information. The Internet website operably associated with digital engine 101 allows a user to select information to be wirelessly communicated to electronic device 105 utilizing a network environment. The Internet website may include several different types of information related to audio information. FIGURE 4, described in greater detail below, illustrates one embodiment of providing an

Internet website for displaying selectable audio information. For example, the Internet website may include music and/or artist search engines, playlists, top 10 charts, artists by genre, and other information associated with audio information. A user may select information associated with the audio information and digital engine 101 can maintain the information or data associated with the selected information in a digital format. Communications engine 102 coupled to digital engine 101 may wirelessly communicate data associated with the selected audio information to electronic device 103. Therefore, a user may access and select audio information via an Internet website and wirelessly communicate the data to an electronic device. As such, system 100 advantageously allows for wireless communication of selected audio information to electronic devices that may be remotely located from a conventional terrestrial communication network.

Electronic device 105 may be configured in a plurality of ways for receiving wireless communication of selected audio information. In one embodiment, electronic device 105 may be operable as a component configured to receive a cellular signal comprising the selected information communicated by the communication engine. For example, a device having a cellular modem may be operable to receive the information at specified intervals. Upon receiving the information the electronic device may process the received information. Electronic devices are described in more detail below and may include a network radio, a modular device, an audio system, a personal digital assistant (PDA), a cellular phone, or other electronic devices operable to receive

information wirelessly communicated by communication engine 102.

Communications engine 102 may be operable to wirelessly communicate selected information to electronic device 103 in a plurality of ways. The present invention advantageously allows for several different embodiments of wirelessly communicating selected audio information to electronic device 103 and is not limited to any specific configuration described below.

Several different types or combinations of wireless communication may be realized by the present invention. Communications engine 102 may be operable to wirelessly communicate the selected information from a information network, such as the Internet, to an electronic device operable to receive wireless communications. In one embodiment, communications engine 102 may comprise a conduit to interface information with a wireless communication network. The conduit may configure the information located within the information network into a format operable to be transmitted via wireless communication. For example, a wireless device may be operable to receive packets of information having a specific size and in a specific format. In such an embodiment, communications engine 102 could format the information into a desirable format for wirelessly communicating the information to electronic device 103.

Several types of wireless communication may be used by communications engine 102 to communicate the selected information to an electronic device. Communications networks such as GSM, Digital Satellite communication, SB, Radio bands, DRC, SuperDRC or other systems or types of transmission such as TDMA, CDMA, spread spectrum, etc.



or frequencies such as between about 1.7 GHz and 2.0 GHz may be realized by the present invention for communicating information or data representing the selected audio information to electronic device 103.

5           In one embodiment, the selective information may be communicated using a digital broadcast signal. Digital broadcast includes providing information via a signal such as AM, FM, and the like. Digital information may be included or encoded as a sub-carrier within the broadcast  
10       signal and received by electronic device 103. A digital sub-carrier may include a selective bandwidth of frequencies for a specific radio station (i.e. 6 MHz for FM). The selective information may be wirelessly communicated to electronic device 103 utilizing a  
15       communication engine 102 operable to communicate the selective information via a digital FM signal. In this manner, selective information may be communicated within digital FM sub-carriers to an electronic device operable to receive the information. For example, a user may  
20       subscribe to communicate the information via an FM sub-carrier and receive the selective data through wireless communication via a specified FM sub-carrier.

          In one embodiment, the selected information may be formatted and transmitted to achieve a desirable  
25       transmission rate. For example, conventional systems may transmit information at a speed of 10 kilobits per second. Therefore, for 1 megabyte of information to be communicated to an electronic device, a transmission time of approximately 800 seconds may be required. The  
30       present invention may allow for a relative increase in transmission speed by removing the requirement that information be communicated asynchronously to an

electronic device. For example, conventional wireless communication utilize a specified frequency to communicate information in two directions (i.e. cellular phones). As such, information is communicated across a channel in an asynchronous manner to provide a continuous audio signal to the recipient. The present invention advantageously allows for signals to be transmitted to an electronic device in a less than asynchronous manner. For example, if a user selected a song to be wirelessly communicated to an electronic device, system 100 could communicate the information in a less than asynchronous manner allowing the selected information to be transmitted efficiently thereby decreasing the overall download time for the selected audio information.

In one embodiment, the selected information may be compressed and transmitted across the same frequency but at different phases thereby allowing plural signals having different phases to be wirelessly communicated to an electronic device. Therefore, the electronic device may be operable to receive multiple phased signals and process the selective information accordingly.

In one embodiment, the information may be wirelessly communicated at a relatively slow transmission rate. For example, a user may schedule when the selected audio information may be used by electronic device 103. The user may select several different audio tracks or songs to be transmitted to an electronic device associated with the user's vehicle such that the user can listen to the user selected audio information during the drive home at the end of a work day. Therefore, it may be desirable to utilize a slower transfer speed due to the extended amount of time available prior to actual use of the

selected audio information. In this manner, communications networks having less or slower transfer rates may be used to wirelessly communicate the selected audio information to the electronic device.

5 In another embodiment, high speed wireless communication networks may be used to communicate the selected audio information. For example, a user may want to listen to an Internet broadcast of an Internet radio station. Therefore, high speed communication may be  
10 required to wirelessly communicate or stream the selected audio information to an electronic device.

In another embodiment, a hybrid of wireless communication rates may be deployed depending on the requirements of the selected audio information and/or the  
15 electronic device. For example, the selected audio information may first be transmitted to the electronic device via high speed communication until enough information has been wirelessly communicated and buffered into a memory device operably associated with the  
20 electronic device. Upon communicating a certain percentage of the selected audio information, slower communication speeds may then be used to communicate additional selected audio information.

Therefore, system 100 may be configured in a  
25 plurality of ways to communicate selected information to electronic device 103. Digital engine 101 may be used to maintain data or information associated with the selected information and communication engine 102, communicatively coupled to digital engine 101, may wirelessly  
30 communicate selected information to electronic device 103.

FIGURE 2 illustrates a block diagram of a method of wirelessly communicating selected information to an electronic device. The method may be used in association with the system illustrated in FIGURE 1 or other systems operable to utilize the method of FIGURE 2.

The method begins generally at step 200. At step 201 selectable audio information may be accessed utilizing a network communications device. For example, selectable audio information may be displayed at an Internet website accessible by a personal computer. In another embodiment, the selectable information may be accessed utilizing a wireless communications device such as, a cellular phone, a PDA device, or other devices operable to provide access to the selectable audio information. Upon accessing the selectable information, the method proceeds to step 202 where a user can identify or select audio information to be wirelessly communicated to an electronic device. For example, a user may select a entire album to be wirelessly communicated to a PDA device.

Upon the user selecting the audio information, the method proceeds to step 203 where the method maintains information associated with the selected information. In one embodiment, the information may be an audio file, such as a wave file, and MP3 file, etc. representative of the selected audio information. In another embodiment, a network location that comprises a file representing the selected information may be maintained. Another example may include a network location of a network broadcast of audio information. Therefore, the method at step 203 may maintain several different types of information associated with the selected audio information.

Upon maintaining information or data associated with the selected information, the method proceeds to step 204 where the method wirelessly communicates information associated with the selected information to an electronic device. For example, if an audio file associated with the selected audio information was maintained, the method would communicate the audio file to the electronic device. In another embodiment, a link or network address broadcasting the selected audio information may be accessed and, at step 204, wirelessly communicated to an electronic device. In another embodiment, a combination of different types of audio information may be wirelessly communicated to an electronic device. Upon transmitting the selected audio information, the method proceeds to step 205 where the method ends.

Selected audio information may be communicated in a plurality of ways as described above including communicating via a cellular communications network to an electronic device operable to receive cellularly communicated signals. For example, the information may be selected from a website operable to display selectable information. Upon selecting the audio information, a data file representing the selected audio information may be wirelessly communicated to an electronic device thereby allowing a user to select audio information via the Internet and wirelessly communicate the information to an electronic device. In some embodiments, the wireless communication to an electronic device may occur in an off-line environment. For example, a user may go "off-line" to access a website and select information and then go "off-line" or end the browsing session. The wireless communication may then occur while the user is

off-line thereby removing the confines of using an active or on-line browsing environment (i.e. Internet radio broadcast, streaming audio, etc.) for accessing selected information.

5           Therefore, the method of FIGURE 2 allows for information, such as audio information, to be communicated from a network location such as a web site, to an electronic device via wireless communication. The present invention advantageously allows users to access  
10       and download information accessible by a network location to an electronic device operable to receive wireless communications thereby reducing the need for land lines, terrestrial communication networks, etc. for communicating selective information.

15           In one embodiment, the method of FIGURE 2 may be deployed in association with a Internet website operable to display selectable links for downloading information. The information may include audio information such as MP3's, streaming audio, streaming, Internet broadcasts,  
20       etc. selectable by a user and operable to be wirelessly communicated to an electronic device. By providing a user with a website of selectable audio information operable to be wireless communicated to an electronic device, a user may customize information communicated to  
25       an electronic device. In one embodiment, a user may communicate information to an electronic device that may not be owned by the user. For example the method of FIGURE 2 could be modified to allow a user to wirelessly communicate audio information to a plurality of  
30       electronic devices that may or may not be owned by the user.

FIGURE 3 illustrates an electronic device operable to receive selected audio information in accordance with the teachings of the present invention. Electronic device 300 includes a communication module 301 such as a transceiver coupled to storage medium 302 such as a high speed buffer, programmable memory, or other devices operable to store information. Electronic device 300 may also include processor 302 operably associated with communication module 301 and storage medium 302. Processor 302 may be operable to process wirelessly communicated selected information and in one embodiment may be integrated as part of communication module 301 of storage medium 302. In the same manner, as larger scale integration of electronic devices proliferate, communication module 301, processor 302, and storage medium 303 may be integrated into one communication component or device operable as electronic device 300.

Processor 302 may be operable using software that may be stored within storage medium 302. In one embodiment, software upgrades may be communicated to electronic device 300 via wireless communication allowing for efficient system upgrades for electronic device 300. Storage medium 302 may include one or several different types of storage devices. For example, storage medium 302 may include programmable gate arrays, ROM devices, RAM devices, EEPROMs, minidisks or other memory devices operable to store information.

During use, electronic device 300 receives wireless communications of selective information. The information may be transmitted via a wireless communications network and received by electronic device 300 via transceiver 301. Transceiver 301 may be operable to convert the

received wireless communication signal into a desirable format and store the received information within storage medium 302. The received information may then be processed by electronic device 300.

5           In one embodiment, electronic device 300 may be operable as an audio player configured to play digital representations of music. For example, electronic device 300 may also include an MP3 player operable to process the received information into an audio signal.

10          Therefore, electronic device 300 may be used to receive wirelessly communicated MP3 audio files and play these files using an MP3 player when desired.

          In another embodiment, electronic device 300 may be configured as a PDA wherein the PDA includes a web browser operable to wirelessly communicate with the Internet. The PDA device may include a user interface allowing a user to select information to be wirelessly communicated to electronic device 300. By providing a website of selectable information, the PDA devices may provide an efficient embodiment for electronic device 300 in that it allows a user to access and select information using a wireless communication network and receive the selected information using the same or different wireless communication network.

25           In yet another embodiment, electronic device 300 may be configured as a component operable to receive selective information via wireless communication and communicate the information to a second electronic device such as an automobile sound system, home stereo, etc.

30          For example, electronic device 300 may utilize transceiver 301 to receive wirelessly communicated information. Electronic device 300 may then be coupled to



an automobile sound system using an interface and  
communicate the received information to the automobile  
sound system. In this manner, electronic device 300 may  
be used to provide the automobile sound system with audio  
files received via wireless communication.

In another embodiment, electronic device 300 may be  
operable to communicate the received audio information to  
an audio system via a localized communications signaling  
network. One such network may include utilizing  
'Bluetooth' communication standard used to provide  
communication between electronic devices in a proximal  
setting.

In one embodiment, electronic device 300 may be  
integrated into an audio component such as a radio  
receiver. Electronic device 300 integrated into an audio  
component may be configured to process digital audio  
files wirelessly communicated to an audio component.

In another embodiment, electronic device 300 may be  
operable to communicate with an analog receiver at a  
predetermined frequency. For example, a specific  
frequency may be selected (i.e. 93.7 MHz) for  
communicating the wireless received selected information  
from electronic device 300 to a localized audio system.  
Electronic device 300 communication of the wirelessly  
received information allows a conventional receiver to  
receive the selected audio information. In one  
embodiment, the conventional receiver may be configured  
to receive a digital sub-carrier, on-carrier, or other  
within a specified frequency. Therefore, electronic  
device 300 may be operable to locally transmit the signal  
at a specific frequency thereby allowing the conventional  
receiver to receive the information.

In another embodiment, electronic device 300 may be operable to scan plural bandwidths to receive the selective information. For example, transceiver 301 may be operable to receive selective information across  
5 several frequencies and process the received information accordingly.

In another embodiment, electronic device 300 may be operable to scan several frequencies to obtain the desirable information. For example, a user may select  
10 several Internet broadcasts comprised of streaming audio information. Therefore, the information may be transmitted across several wireless frequencies receivable by electronic device 300. Electronic device  
15 300 may then be operable to allow a user to scan wirelessly communicated Internet broadcast signals thereby providing a user selected virtual broadcast radio network.

In another embodiment, electronic device 300 may include a user interface operable to communicate with a  
20 an Internet website operable to display selectable audio information. The Internet website may be configured as a user preferred environment displaying a users selected audio information, Internet broadcast selections, streaming audio selections, etc. With a display device  
25 for displaying a Website having selectable information, electronic device 300 may allow a user to select audio information via a user interface and receive the selected information via wireless communication thereby providing a customizable WebRadio device for the user.

In another embodiment, electronic device 300 may be  
30 a modular device configured to be coupled to, for example, a portion of a cars interior. For example,

electronic device 300 may be mounted to a portion of a car's console thereby providing a removably coupled electronic device operable to wirelessly receive selected audio information. As a removable device, electronic  
5 device 300 may be also be coupled to a home audio system, a portable radio system or other systems thereby providing a versatile electronic device operable to receive wirelessly communicated selected audio information.

10 In another embodiment, electronic device 300 may be operable as a PDA and/or a cellular phone that may be mounted to an automobile's console. Electronic device 300 may then integrate with a user's automobile to provide an all encompassing communications device. For  
15 example, electronic device 300 configured as a PDA and cellular phone may allow for communication with a users email account, voice mail account, the Internet, as well as allowing for the receipt of selected audio information via wireless communication. Electronic device 300 may be  
20 operable in a hands-free mode allowing a user to maintain safe driving fundamentals. During use, electronic device 300 may be processing selective audio information for communicating with an automobile audio system and may further be operating to receive incoming cellular calls.  
25 Electronic device 300 may be set-up by the user to pause the music being played and allow the received cellular call to be communicated either via an independent speaker or utilizing the automobiles audio system. Additionally, electronic device 300 may be operable to adjust the  
30 listening level of an automobiles audio system, play received voice mail messages, allow a user to view the Internet, etc.

In one embodiment, electronic device 300 may be operable as a dual mode electronic device capable of receiving both digital and analog wireless communication signals. In this manner, electronic device may efficiently utilize available bandwidth for receiving selected information from a communications engine. For example, transceiver 301 may be a wireless communications modem operable to receive digital or analog signals.

FIGURE 4 illustrates a graphical user interface (GUI) for displaying selectable audio information according to one aspect of the present invention. The GUI may be operable with a computer system, cellular device, PDA, or other electronic devices or systems operable to display the GUI of FIGURE 4.

The GUI, shown generally at 400, may be displayed using a conventional web browser 402 such as MICROSOFT's INTERNET EXPLORER, a WAP browser, or other browsers operable to display the audio information. Browser 402 includes browser functions, shown collectively at 403, for navigating a network such as the Internet or an intranet. Homepage 401 may be displayed using browser 402 and may include several functions, features, information, etc. related to audio information. Home page 402 may be developed using several different types of programming (i.e. HTML, XML, Java, etc.) used to developing a network location or web-site. The present invention is not limited to any one specific type of software and may be realized in plurality of ways as can be appreciated by those skilled in the art.

Homepage 401 may also include Log-in region 410 allowing a user to log into homepage 401 and display a user preferred environment. For example, a user may want

Radio Dial 412 to appear when a user logs into homepage 401. In another embodiment, a user may want to view a current playlist selected by the user or the status of wirelessly communicated playlist. A user may also  
5 provide demographic information allowing advertisers to access the demographic information and provide advertisements based upon the demographic information. For example, an advertiser may want to target Hispanic females in the 21-25 year old age group. Through  
10 providing demographic information to advertisers, when a user logs into homepage 401 selective advertising can be "targeted" for a group of users.

Homepage 401 may also include several tabs for efficiently navigating homepage 401. Library tab 405 may  
15 be provided to allow a user to browse available audio information that may be presented by title, genre, artist, decade, culture, etc. Store tab 407 may also be provided for locating items available for purchase such as CDs, PDA devices, MP3 players, wireless communication  
20 hardware, interfaces, software or other types of products that may be purchased while on-line. Chat tab 408 may also be provided allowing a user to chat with other user's of home page 401. For example, a guest musical artist may be available to chat with visitors of home  
25 page 401 via chat page associated with chat tab 408. Home page 401 may also include contest tab 409 for displaying current contests, prizes, and/or winners.

Radio tab 406 may also be provided for displaying audio information. For example, radio tab 406 may  
30 display a collective menu 411 of selectable functions or features associated with audio information. Top ten lists may be provided to a user based on several

different billboard polls or genres. A search engine may be provided allowing a user to search for a specific type of audio information such as an artist, song title, genre, Internet radio station, etc. In one embodiment, a user may input the lyrics to a song within the search engine. As such, the search engine may locate several different songs having the desirable lyrics and allow a user to select the search results. A user may also use a select a device feature that allows a user to select a destination device for communicating selected audio information. For example, a user may want to communicate a playlist to several different devices such as a PDA, a home computer system, a work computer system, etc. As such, a user can communicate selective information to several devices without having to download the information separately for each device.

A send a friend link may also be provided allowing a user to send selective audio information to a friend's electronic device. A user may also join a group comprised of individuals that select a certain genre of music to be communicated to the user's electronic device. For example, a user may want to join a group that plays only 50's swing music. As such, the user could communicate the group's selected songs to the user's electronic device. A user may also utilize an email account provided by homepage 401 allowing a user to correspond with others via email. A user may also access a list of guest DJ's that may provide playlists of songs chosen by the guest DJ and selectable by a user.

In one embodiment, a user's radio dial 412 may be provided when a registered user logs into homepage 401. As such, radio dial 412 may include several functional

buttons similar to conventional systems such as a volume control and a station control. However, radio dial 412 surpasses the limitations of conventional systems through providing a programmable radio dial of user customized audio information. Radio dial 412 includes several stations that may be programmed using program interface 413. The preset stations may include several different types of user customized preset information such as user selected playlists, internet broadcast stations, top 10 lists, group playlists, artist's selected lists, on-line radio station, conventional radio stations, Internet phone, cellular phone, etc. and other functions, features, or information associated with audio information.

Radio dial 412 may also be displayed as a separate user interface and in some embodiments, does not require a 'browsing' environment to view radio dial 412. For example, an electronic device, such as a PDA, having a display may graphically present radio dial 412 to a user. One example may be using electronic device in association with an automobile audio system. Electronic device may display radio dial 412 and may allow a user to navigate, modify, select, adjust volume, access daytimer, access phone lists, etc. or perform other functions while the electronic device is used in association with an automobile sound system. Therefore, radio dial 412 may be operable as an application for use with several different types of electronic devices (i.e. computer systems, portable computing devices, cellular phones, etc.) operable to display radio dial 412 and in some embodiments may be wirelessly communicated to an electronic device.

In another embodiment, homepage 401 may allow a user to select when to download the information to an electronic device. For example, a user may want to listen to a certain genre of music at a specific time of day thereby allowing a user to select the information. As such, a user may select a different playlist for every day of the week thereby allowing a user to listen to different songs on different days of the week. The user can further identify when the selected playlist should be available for listening. For example, if a user wanted to listen to "playlist #1" on Monday morning during the drive into work between 8:00 am and 9:00 am, the user would enter the time and the day playlist #1 would be available for listening. In this manner, the playlist may be communicated to the electronic device thereby allowing a user to listen to selective audio information at a desirable time.

FIGURE 5A illustrates a portable radio system having a mount for an electronic device according to one embodiment of the present invention. Portable radio 500 includes a mount 501 operable to receive electronic device 502. Mount 501 may include a connector operable to provide communications and power to electronic device 502. During use, electronic device 502 when mounted within portable radio 500 communicates with portable radio to provide remotely received selective audio information.

In one embodiment, electronic device 502 may include a user interface allowing a user to access the Internet. Therefore, selective audio information located on the Internet may be accessed by the user and remotely



communicated to electronic device 502 coupled to portable radio 500.

In another embodiment, portable radio 500 may include memory operably located within for storing downloaded information. For example, portable radio 500 may include 32 MB of RAM allowing electronic device 502 to receive selective information and download the selective information to memory located within portable radio 500. In this manner, the downloaded music may be operable to be played within portable radio 500 while allowing electronic device to be removed from portable radio 500.

Therefore, portable radio 500 including electronic device 502 allows a user to communicate selected audio information to portable radio 500.

FIGURE 5B illustrates automobile console having a mount for coupling an electronic device according to one aspect of the present invention. Console 510 includes mount 511 operable to receive electronic device 512. Mount 511 may be located in many different locations within an automobile such as coupled to a sun visor, center console, dash board, floor board, etc. Mount 511 allows the user to couple electronic device 512 to the automobile and provide an interface for communication between electronic device 512 and the automobile audio system. Mount 511 may also include a power connection that allows electronic device 512 to use the automobiles power during use. The power connection may also be used in association with a recharging circuit operable to recharge a power supply within the electronic device.

During operation, electronic device 512 coupled to mount 511 may receive selected audio information via

wireless communication and communicate the selective information to the automobile audio system. In one embodiment, the automobile may include memory operable associated with the automobile for storing information. The memory may be used in association with mount 511 and electronic device 512 to store the selected audio information. In this manner, voluminous audio information can be stored within the memory allowing electronic device 512 to receive additional information.

In one embodiment, a mount may be provided for a home audio system (not shown) for downloading selected audio information for use with a home audio system. For example, a mount device may be coupled to a home stereo system such that the upon placing an electronic device such as electronic device 500 within the mount, selected audio information may be communicated to the home audio system thereby allowing a home audio system to be used in association with an electronic device.

FIGURE 6 illustrates a block diagram of a system for communicating voice mail messages using email according to one embodiment of the present invention. The system, indicated generally at 600, includes email server 601 coupled to a voice mail storage device 602. System 600 further includes a computer system or network terminal 603 such as a computer coupled to network 604. System 600 further includes mount 605 for mounting electronic device 606 for hardwire communication of information. Device 606 may also communicate with network 604 using a wirelessly communication network operably associated with network 604 and coupled, for example, via tower 607.

During operation, system 600 communicates voice mail messages to a user utilizing email server 601. For

example, if a user receives a voice mail message, email server 601 would be notified and a voice mail message would be sent to the user's email account in the form of an email message. For example, a voice mail message  
5 would be sent to a user's email account within intranet 604 in the form of an audio file as an attachment to the email. Upon receiving the email, a user may click on the audio file representing the voice mail message to hear the message left by a caller.

10 In one embodiment, a user may be accessing the Internet via a phone line and, as such, be unable to receive notification that a voice mail message has been received. System 600 would receive the voice mail message and send an email comprising the voice mail  
15 message to the user email account. In this manner, a user can remain connected to the network and receive voice mail without having to log off or disconnect from the Internet.

In one embodiment, a user may receive the voice mail  
20 message via a portable electronic device. For example, a user may be using remote device 605 operable to receive wirelessly communicated information. System 600 would receive the voice mail message and forward the voice mail message to a user's portable electronic device 606. In  
25 this manner, a user may be capable of receiving voice emails at remote locations.

In another embodiment, a user may subscribe to use an Internet email account that may be operably associated with system 600. Utilizing an Internet email account may  
30 allow a user the flexibility to check voice email messages from any location in the world. For example, a user may access a "Hotmail" email account while traveling

on business in a foreign country. The user, upon gaining access to the "Hotmail" account, would be able to listen to voice mail messages sent to the user via the "Hotmail" email account.

5           Through utilizing an email account to receive voice mail messages, a user may be afforded great flexibility in communicating voice mail messages. For example, a user may be able to forward a voice mail message received in the form of an email to one or a plurality of other  
10       email accounts. In this manner, a voice email message may be sent efficiently to other email users. For example, a user may maintain a distribution list of individuals working on a particular project that may have a need to hear certain voice email messages. In this  
15       manner, a user may efficiently disseminate information to other individuals while adding additional textual information to the body of the email allowing a user to comment on the original voice email message.

          In another embodiment, a user may forward a received  
20       voice email message to another account operable to receive forwarded voice email messages. For example, system 600 may be operable to receive an email message having a voice mail message as an attachment. The system would then be operable to forward the voice mail message  
25       to specified phone number, separate email account, and/or voice mail account, etc. thereby providing a user flexibility in receiving voice email.

          In one embodiment, a user may utilize an email account to establish an answering service for voice  
30       mails. For example, a user's telephone number may be operable with an email account to provide an answering service. A user may record a message for a specified

phone number or extension and, upon receiving an incoming call, the recorded message may be played back to incoming call's initiator. System 600 would then forward the received voice email message via an email account to the user. For example, a user may have an account set up at a home residence for receiving voicemail messages via a user defined email account. The user could then forward all received voice mails from the home account to an email account at a place of work. Therefore, the user may have complete access to received voicemail messages. In the same manner, a user could set up their work phone number to forward an voice email messages to the users home email account thereby allowing a user to receive voice email at a home email account.

Therefore, system 600 may be operable in a plurality of ways to provide email messages comprised of voicemail messages received via a voice mail or email account.

FIGURE 7 illustrates a flow chart for providing voice email messages according to one embodiment of the present invention. The method begins at step 701 where a voice mail message is left for a user. The message could be at a residence, place of business, etc. The method then proceeds to step 702 where the message may be stored as an audio file within a database operable to store a file comprised of the voice mail message. Upon storing the file, the method proceeds to step 703 where an electronic mail message may be generated. The electronic mail message may be addressed to the recipient of the voice mail message. The method then proceeds to step 704 where the audio file representing the voice mail message is attached to the electronic message.

Upon attaching the audio file, the method then proceeds to step 705 where the email message may be sent to the email address. Upon sending the email message the method proceeds to step 706 where the method determines  
5 if the email message should be sent to a wireless electronic device. If the message is not to be sent to a wireless device, the method proceeds to step 720 where the method ends. If the message is to be sent to a wireless electronic device, the method proceeds to step  
10 707 where a signal may be sent to the wireless electronic device and at step 708 an indication is provided to the electronic device indicating that a voice email message has been received via a user's email account. The method may then proceed to step 709 where the user decides  
15 whether or not to listen to the voice email message. If the user decides not to listen to the voice email message, the method may proceed to step 710 where the method ends. If the user decides to listen to the voice email message, the method proceeds to step 711 where a  
20 request may be sent by the electronic device requesting the voice email message be forwarded to the user's electronic device. At step 712, the voice email message may be sent to the user's electronic device. Upon forwarding the voicemail message to the user the method  
25 may proceed to step 720 where the method ends.

As such, FIGURE 7 depicts one method of providing an email message comprised of a voice mail message. Certainly, other methods may be deployed as advancements in technology are made without departing for the spirit  
30 and scope of the present invention.

FIGURE 8 illustrates a flow diagram of a method for providing selected audio information to an electronic

device according to one embodiment of the present invention. The method begins at step 800 where a user accesses a webpage via the Internet. The webpage may be a home page illustrated in FIGURE 4 or other web pages operable to display selectable references to audio information. The method proceeds to step 801 where a user selects desirable audio information. For example, a user may select a single song, a plurality different songs, an entire album, a broadcast station, streaming audio, etc. or other selectable audio information. Upon the user selecting a reference to audio information, the method may proceed to step 802 where a playlist may be created that represents the user's selected audio information. The playlist may be variable in size and comprised of a plurality of different types of available audio information. Upon creating a playlist, the method may proceed to step 803 where information associated with the playlist is obtained. For example, a list of network or URL locations comprised of the desirable audio information may be obtained. In this manner, desirable audio information may be obtained from many different sources such as URLs, network addresses, hard drives, databases comprised of audio information, etc. The sources may be accessed to obtain the selected audio information.

Upon obtaining data associated with the customized playlist, the method may proceed to step 804 where the user is prompted for a destination for the playlist. For example, a user may want to communicate the selected audio information to a remote electronic device, a automobile audio system, a home stereo system, a home computer, an electronic device coupled to a home network

or computer system, etc. or other locations or devices operable to receive the selected audio information. In one embodiment, a user may select a device owned by a friend to accept the selected audio information. For  
5 example, a husband may want to send a romantic playlist to his wife on their anniversary. In this situation, the husband would select his wife's electronic device as the receiving device for the selected audio information.

Upon selecting a device, the method proceeds to step  
10 805 where the method determines the destination of the selected audio information. If the information is to be sent to a device requiring wireless communication, the method proceeds to step 806 where the information is formatted for communicating the information to a wireless  
15 electronic device. For example, a wireless PDA device may be selected as a destination device for the selected audio information. The PDA device may include an audio player, such as an MP3 player operable to play or execute MP3 audio files. In such an embodiment, the method could  
20 format the information such that the information may be wirelessly communicated and subsequently played by the MP3 player.

Upon formatting the information, the method may then proceed to step 807 where the audio information is  
25 wirelessly communicated to the selected device. In some embodiments, the device may be operable to receive a limited amount of information based upon storage capacity of the device (i.e., 16 Megabytes). In such a case, the method may divide the information into component parts  
30 and periodically communicate the component parts, such as packets, to the electronic device. Upon communicating the audio information, the method may then proceed to



step 808 where the signal may be received by the destination or electronic device. The method may then proceed to step 809 where the method determines if all of the audio information has been received. For example, if  
5 16 Mbytes or 32 Mbytes of selected audio information was initially transmitted due to capacity limitations of the selected device, the method may query the selected device to determine if capacity is available. If available memory exists, the method may proceed to step 807 where  
10 the method may communicate additional audio information based upon the amount of available memory. The method repeats until all of the selected audio information has been transmitted.

Upon communicating the selected information, the  
15 method may proceed to step 810 where the playlist may be executed. For example, a user may select a continuous communication of selected audio information (e.g. several hours of music, Internet broadcast, etc.). As such, the method may continuously play or execute the received  
20 audio information. In another embodiment, the method may proceed to step 811 where the method may store or buffer the received information until it is desirable to execute the received selected audio information. As such, upon  
25 executing the selected audio information, the method may proceed to step 809 where the method may repeat.

In one embodiment, a user may elect to download a broadcast of an on-line radio station. For example, a user may want to listen to a radio station located in a remote location wherein conventional radio receivers  
30 could not receive the desired broadcast. For example, a person living in Houston, Texas may not be able to receive a radio broadcast signal from a radio station in

Seattle, Washington utilizing a conventional radio receiver. In accordance with the teachings of the present invention, a user may select an on-line broadcast or radio station as all or a part of the selected audio information. The user may then receive radio broadcasts without having to use a home computer system or conventional radio receiver.

At step 804, a user may select a device that does not require remote communication of information. For example, a user may elect to communicate the selected audio information to device, such as a personal computer, PDA device, MP3 player, etc. coupled via a network connection to the Internet or an Intranet. The user may receive the selected playlist at the determined device for eventual playing. In one embodiment, a user may select a plurality of devices as destination devices for receiving downloads of the selected audio information. For example, the user may want to download the information to a home stereo system, a PDA device, and an automobile stereo. As such, the selected information may be communicated to more than one destination device. In addition, the format of the download may match or conform to the selected destination device(s).

The present invention may be configured in a plurality of ways to communicate desirable audio information to users by allowing users to select desirable audio information and transmitting the desirable audio information to a specified destination thereby allowing a user to receive on-demand customized audio information. Moreover, the download may occur in an off-line environment, allowing a user to enjoy the

selected audio information accessed on-line without having to be on-line or utilizing a browsing environment.

In one embodiment of the present invention, the method of FIGURE 8 may be modified to allow a user to  
5 select a "user group" for receiving customized audio information. For example, a "user group" may include user's that only like to listen to contemporary jazz wherein a user may request a certain song. Therefore, a virtual request line may be created for a specific genre  
10 of music allowing "members" to transmit audio information to the "group".

In another embodiment of the present invention, the method may be modified to allow a user to select a specific genre to be transmitted to the users device.  
15 For example, a user may elect to have random country and western music transmitted to a destination device. The user could efficiently create a radio station format and have the format received at a destination device.

In a further embodiment, a user may select a group  
20 of genres to be downloaded to a desirable device. As such, the method may be modified to allow a user to select several different genres to download random music within the specified genres.

In another embodiment, a user may elect to download  
25 the same music as another individual. For example, a user may want to download the same music as their best friend. Therefore the user could elect to download the same music as their friend or group of friends. In another example, a user may want to listen to the same  
30 music that an artist listens to on a specific weekday of evening. For example, a user may want to listen to the same music that Barry White listens to on a Saturday

night. Therefore, the user may select "Barry White's" Saturday night playlist and receive the same playlist Barry White receives on Saturday night.

5 In another embodiment, the method of FIGURE 8 may be modified to allow a user to manipulate songs post download. For example, a user may want to store, delete, replay, copy, forward, etc. received audio information. Therefore, the method of FIGURE 4 may be modified such that a user can manipulate or process the received audio  
10 information in a plurality of ways.

In one embodiment of the present invention, an on-line radio station may be provided. For example, the radio station may be created for transmitting audio or on-line broadcasts. The on-line broadcaster's or hosts  
15 may create their own format for broadcast. For example, an on-line radio station may be provided that transmits only children's songs. Prior to conception of the present invention, conventional radio stations could not afford to transmit music such as children's songs to  
20 conventional radio receivers. The present invention, by providing a medium for transmitting selectable audio information, enables the existence of on-line broadcasting with little or no overhead for a host. A user may select an on-line broadcast for on-line or off-  
25 line delivery.

In another embodiment, on-line broadcast of audio information representing books or novels may be provided to individuals such as the visually impaired. For example, an on-line broadcast station may provide  
30 several hours of audio information broadcast representing books or novels to be broadcast with very little overhead.

FIGURE 9 illustrates an automobile console having a mount for an electronic device according to one embodiment of the present invention. Console 900 includes a conventional audio system 901 comprised of a receiver 902 and CD player 903. Interface 904 may be coupled to audio system 901 via plug 905 and cable 908, which may be coupled to an auxiliary line into audio system 901. Interface 904 may also include contact 906 for contacting electronic device 907. Cable 908 may be a multiple conductive cable for providing power from the automobiles power system via a protection circuit or fuse 909 for powering electronic device 907. In one embodiment, interface 904 may be operable to recharge electronic device 907 utilizing a power source associated with an automobile.

During operation, electronic device 907 may be mounted within interface 904. Electronic device 907 may also be powered or recharged via power line 910 and communicate with the systems audio system via interface cable or bus line 911. Audio information communicated to electronic device 907 may be transferred to audio system 901 such that a user may listen to selected audio information. For example, a user may have previously selected a plurality of audio files to be transmitted to electronic device 907. Electronic device 905 may communicate the selected audio information to the automobiles audio system utilizing interface 901 thereby allowing the user to listen to selected audio information. In one embodiment, cable 908 may be custom installed to audio system 901. For example, the cable may be coupled to an auxiliary line for the system's radio or may be coupled to CD player line 912. In

another embodiment, a radio manufacturer may provide interface 904 as a standard interface integrated into the audio system thereby allowing communication between electronic device 907, audio system 901 and/or console 900.

Electronic device 907 may include a plurality of different types of devices. For example, electronic device 907 may include a PDA device operable to store selected audio information. The information may be either remotely downloaded using an Internet web browser and wireless communication to the PDA device. In another embodiment, selected audio information may communicated to a PDA device via a hard wire coupled to a computer system interfacing with the Internet.

In another embodiment, electronic device 907 may include an audio file player operable to play audio files such as MP3's, etc. The audio files may be remotely or locally communicated to electronic device 907 and upon coupling to audio system 901, the audio files may be transmitted to audio system 901 in a form receivable by audio system 901.

Although the disclosed embodiments have been described in detail, it should be understood that various changes, substitutions and alterations can be made to the embodiments without departing from their spirit and scope.

WHAT IS CLAIMED IS:

1. A system for communicating selected information to an electronic device, the system comprising:

a digital engine operable to maintain data associated with selected audio information; and

a communication engine communicatively coupled to the digital engine, the communication engine operable to initiate wireless communication of the data to the electronic device.

2. The system of Claim 1 further comprising an interface operably coupled to the digital engine, the interface operable to provide available information to a user of a communication network, and to receive an input from the user identifying the selected information.

3. The system of Claim 2, wherein the interface operates in a browsing environment and the wireless communication operates outside the browsing environment.

4. The system of Claim 1, wherein the wireless communication comprises communicating via a cellular communications network.

5. The system of Claim 4, wherein the cellular communication network comprises a global system for mobile communications network.

6. The system of Claim 5, wherein the global system for mobile communications network operates between about 1.7 GHz and 2.0 GHz.

7. The system of Claim 4, wherein the cellular communication network comprises a code-division multiple access network.

5 8. The system of Claim 1, wherein the wireless communication comprises communicating via a high-speed, low-power microwave wireless link.

10 9. The system of Claim 8, wherein the wireless link comprises a Bluetooth link.

15 10. The system of Claim 8, wherein the wireless link operates around 2.4 GHz.



11. A method for communicating selected audio information to an electronic device, the method comprising:

maintaining data associated with the selected audio information using a digital engine; and  
initiating wireless communication of the data to the electronic device.

12. The method of Claim 11 further comprising:

presenting information associated with audio information within an interface associated with a communication network; and

receiving an input from a user identifying the selected information.

13. The method of Claim 11 further comprising:

presenting information associated with the electronic device; and

receiving an input from a user identifying the electronic device.

14. The method of Claim 12 wherein the interface operates in a browsing environment and the wireless communication operates outside the browsing environment.

15. The method of Claim 11 wherein the wireless communication comprises communicating via a cellular communications network.

16. An electronic device for receiving selected audio information via wireless communication, the device comprising:

5 a communication module operable to receive wireless communication of the selected audio information;

a storage medium operably coupled to the communication module, the storage medium operable to store the selected audio information; and

10 a processor module coupled to the communication module, the processor module operable to process the received selected audio information.

15 17. The device as recited in Claim 16, wherein the communication module comprises a cellular modem.

18. The device as recited in Claim 16, wherein the device is a handheld computing device.

20 19. The device as recited in Claim 18 wherein the handheld computing device is a personal digital assistant (PDA) .

25 20. The device as recited in Claim 16 further comprising software for processing the selected information.

21. The device as recited in Claim 16, wherein the communications module is operable to scan frequencies.

30 22. The device as recited in Claim 16, further comprising a display operable to display a user interface.

PATENT APPLICATION

5

23. The device as recited in Claim 16 wherein the communication module is operable with a 'Bluetooth' communication standard.

24. A method for communicating selected audio information to an electronic device, the method comprising:

5       presenting information associated with audio information within an interface associated with a communication network;

          receiving an input from a user identifying the selected information;

10       maintaining data associated with the selected audio information using digital engine; and

          initiating wireless communication of the data to the electronic device.

25. The method of Claim 24 wherein the interface  
15       operates in a browsing environment and the wireless communication operates outside the browsing environment.

SYSTEM AND METHOD FOR COMMUNICATING  
SELECTED INFORMATION TO AN ELECTRONIC DEVICE

ABSTRACT OF THE DISCLOSURE

Disclosed are a system and method for communicating  
selected information to an electronic device. The  
disclosed system may include a digital engine operable to  
maintain data representing the selected information in a  
digital format. In some embodiments, the digital engine  
may be communicatively coupled to a graphical user  
interface that allows a user to identify the selected  
information. The system may also include a communication  
engine communicatively coupled to the digital engine, the  
communication engine may be operable to wirelessly  
communicate the data representing the selected  
information to an electronic device.

FIG. 1




FIG. 2




FIG. 3






FIG. 4




FIG 5A




FIG 5B







FIG 6









DECLARATION

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name, that I believe I am the original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention or design entitled **System and Method for Communicating Selected Information to an Electronic Device**, the specification of which (check one):

  X   is attached hereto; or

       was filed on                                  as  
Patent Application Serial No.                                   
and was amended on                                 

(if applicable);

that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above; and that I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application(s) for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

<u>Number</u>	<u>Country</u>	<u>Date Filed</u>	<u>Priority Claimed (Yes) (No)</u>
---------------	----------------	-----------------------	--

None.

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application(s) in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

<u>Application</u> <u>Serial Number</u>	<u>Date Filed</u>	<u>Status</u>
--	-------------------	---------------

None.

I declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full name of joint inventor: Russell W. White


Inventor's signature

Date

Residence (City, County, State)

Citizenship

Post Office Address:

  
3/28/00


Austin (Travis County) Texas

United States of America

10704 Redmond  
Austin, Texas 78739



Inventor's signature



Date

March 28, 2000

Residence (City, County, State)

6  
flugerville (Travis County)  
Texas

## Citizenship

United States of America

Post Office Address:

P.O. Box 208

Pflugerville, Texas 78691-0208